



Valere Series

Ki Mobile Induction Cooking Station

The Valere series mobile cooking station is an innovative approach to food preparation. Integrated with state of the art induction appliances, recirculating air-filtration and UL300 fire suppression systems, it eliminates the need for external ventilation. It's a self-contained front-of-house cooking solution that is perfect for hotels, restaurants, resorts, cafeterias, malls, grocery stores and convention centers or anywhere traditional Type-1 hoods and duct-work are impractical or too expensive. It gives food service operators the ability to fully engage their customers, expand their menu and grow their business in areas not possible before. It is a versatile, energy efficient cooking solution that meets NFPA-96 codes and is listed in compliance with ANSI/UL710B and ANSI/NSF standards.

Griddle Features

- ◆ Cooking Surface Width: 34 1/4"
- ◆ Cooking Surface Depth: 18 5/16"
- ◆ Temperature Range: 200° to 450° F
- ◆ 2 Individual positive-off thermostat controls
- ◆ Pre-Heat Time to 400°F: 9 minutes
- ◆ Removable Splash Guard for easy cleanup
- ◆ Removable four-quart front grease drawer

Typical Production:	Per Load	Per Hour
Hamburgers	48	720
Steaks	18	220
Pancakes	35	500
Eggs	45	675

Mobile Cooking Station Features

- ◆ Four-Stage self-contained recirculating air-filtration system for evacuation of grease, smoke, steam, and heat.
- ◆ Buckeye BFR-5 UL300 Fire Suppression System
- ◆ Quiet Blower 55-58 dBA
- ◆ Only 170 CFM of make up air recommended
- ◆ Efficient filtration captures emissions exceeding requirements of NFPA-96 and ANSI/UL710B standards
- ◆ Easy access to filters
- ◆ FLEX— Filter Life Extension Technology (Utilizing intelligent sensors and controls the FLEX system optimizes the air flow and noise levels extending the life of filters up to 200% when compared to fixed flow systems).
- ◆ Solid Stainless Steel construction with standard P-LAM finishes included. Premium panel P-LAM finishes available as an upgrade for front and sides to match adjacent millwork finishes.

Electrical Specifications

- ◆ Plug Type: L15-60P 3 Phase
- ◆ Supply Voltage: 208-240V 3 Phase
- ◆ Installed Appliance Power: 12000W Max
- ◆ 50 Amps

Additional Information

- ◆ 1 Year limited manufacturer warranty
- ◆ Dimensions: H51.5", W59", D35.5"
- ◆ Weight: 705 Lbs
- ◆ ETL Listed in compliance with ANSI/UL710B and ANSI/NSF standards



